

# Technical Data Sheet



## Vision Bretta Blackback

|  |  |                     |            |
|--|--|---------------------|------------|
| Material   | Base: 33% Polyester / 67% Post-Consumer Waste.<br>PU: 100% Virgin.<br>Overall 39% Recycled Content |                     |            |
| Weight<br>acc. to DIN EN 12127   | 260.00   | [g/m <sup>2</sup> ] | + - 5 [%]  |
| Tearing strength   |  |                     |            |
| Elongation at 100 N, longitudinal direction<br>acc. to DIN EN ISO 13934-1        | 6.00   | [%]                 | + - 20 [%] |
| Elongation at 100 N, cross direction<br>acc. to DIN EN ISO 13934-1               | 1.50   | [%]                 | + - 20 [%] |
| Maximum tensile elongation, longitudinal direction<br>acc. to DIN EN ISO 13934-1 | 7.00   | [%]                 | + - 20 [%] |
| Maximum tensile elongation, cross direction<br>acc. to DIN EN ISO 13934-1        | 45.00  | [%]                 | + - 20 [%] |
| Maximum tearing strength, longitudinal direction<br>acc. to DIN EN ISO 13934-1   | min. 350.00  | [N/5 cm]            |            |
| Maximum tearing strength, cross direction<br>acc. to DIN EN ISO 13934-1          | min. 743.00  | [N/5 cm]            |            |
| Flame Retardancy   | B1 / EN13501   |                     |            |



Roseash Limited, Unit B The Height Business Centre, Ibstone Road, Stokenchurch, Buckinghamshire, HP14 3BG  
T: 01494 760240 E: sales@dpm.com W: www.dpm.com