

Technical Data Sheet

Vision Botex

Material	100% Polyester	
Stock widths	app. 320 cm	
Ecology	Öko-Tex Standard 100, product class 2 (Direct Contact with skin)	
Weight		
acc. to DIN EN 12127	210.00 (g/m ²)	+/- 3%
Shrinkage		
Heat shrinkage, 195 degrees, 90sec length acc. to DIN EN 12127	-1.00%	+/- 1%
Heat shrinkage, 195 degrees, 90sec width acc. to DIN EN 12127	-1.00%	+/- 1%
Tearing Strength		
Elongation at 100 N, longitudinal direction acc. to DIN EN ISO 13934-1	21%	+/- 20%
Elongation at 100 N, cross direction acc. to DIN EN ISO 13934-1	24%	+/- 20%
Elongation at 200 N, longitudinal direction acc. to DIN EN ISO 13934-1	39%	+/- 20%
Elongation at 200 N, cross direction acc. to DIN EN ISO 13934-1	28%	+/- 20%
Elongation at 50 N, longitudinal direction acc. to DIN EN ISO 13934-1	11%	+/- 20%
Elongation at 50 N, cross direction acc. to DIN EN ISO 13934-1	20%	+/- 20%
Maximum tensile elongation, longitudinal direction acc. to DIN EN ISO 13934-1	44%	+/- 20%
Maximum tensile elongation, cross direction acc. to DIN EN ISO 13934-1	71%	+/- 20%
Maximum tearing strength, longitudinal direction acc. to DIN EN ISO 13934-1	min. 199 N/5cm	



MADE IN
GERMANY

Roseash Limited, Unit B The Height Business Centre, Ibstone Road, Stokenchurch, Buckinghamshire, HP14 3BG

T: 01494 760240 E: sales@dpm.com W: www.dpm.com